

## PRODUCT INFORMATION

# SYNTEKO TINTING PASTE 1675

## White Wood, Ebenholz, Teak, Rose Wood, Mahogany, Olive and Steel Blue

### GENERAL DESCRIPTION

Synteko Tinting Paste consists of seven different coloured, solventborne pigment pastes to be added to the floor oils Synteko Natural Oil 1608 or Synteko Solid 1612. By adding Synteko Tinting Paste to the floor oil the wooden floor can be coloured as desired while at the same time maintaining all the benefits and excellent properties of the oil. The tinted oil highlights the natural grain of the wood and provides the wood with a clear deep colour.

Synteko Tinting Paste is easily mixed with Synteko Natural or Synteko Solid and comes in tubes for easy dosage and addition.

**Note:** Synteko Tinting Paste must always be mixed with Synteko floor oils prior to application. Please read separate Product Information for Synteko Natural 1608 and Synteko Solid 1612.

TECHNICAL DATA	
Base material	Solventborne pigment dispersion
Coverage*	15-60 m <sup>2</sup> /l (100 ml Synteko tinting paste mixed with 1 L of Synteko Natural 1608 or Synteko Solid 1612.)
Storage	Store frost-free. Must be stored between +5°C (50°F) and +30°C (86°F)
Shelf life	24 months in unopened container (see package)
Cleaning	Clean tools with white spirit (UK). Place used pads, cloths, spillages and waste in a sealed, water filled metal container immediately
Package	100ml

\* Depending on tools and wood species.

### Mixing

Synteko Tinting Paste should be mixed in a ratio of 1 tube (100ml) Tinting Paste to 1 L of Synteko Natural or Solid. The mixing is easily done by adding the tinting paste to the oil and shaking the container thoroughly.

**Note:** Always use full tubes of Synteko Tinting Paste. Be sure to completely empty the tube into the oil in order to avoid colour differences.

### HEALTH & SAFETY INFORMATION


Safety data sheet available for professional user on request. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet) [www.synteko.com](http://www.synteko.com). The following only represents a selection of important information.

**Note:** Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label.

Contains: 2-Butanone oxime May produce an allergic reaction.



Casco Liimid OÜ  
Peterburi tee 101  
13812 Tallinn  
Estonia  
[www.synteko.com](http://www.synteko.com)



*Our information is based on laboratory tests and is considered a guide in connection with the choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.*